

HARVEYPOW





COMPANY
PROFILE

HARVEYPOW

Foshan Haiweineng New Energy Technology Co.,Ltd

HARVEYPOW was established in 2017. A Top Lithium battery manufacturer that focuses on battery system integration R&D and production.

We have impressed countless partners with the most solid product quality. We have more than 10,000 square meters of workshops and more than 200 employees. The monthly production capacity of battery packs can reach 10,000 sets, and 500,000 batteries are used for batteries.

Add.:A006,China Merchants Property, No.26,Guilan North Road,
Nanhai District, Foshan City, Guangdong, China
Factory:Hetai South Road, Hegui Industrial Park, Lishui Town, Nanhai District,
Foshan City, Guangdong , China
Web: <https://harveypoweress.com/>
Email: info@harveypoweress.com

Item No: PS-300/600W-1



Product Specification	
Capacity	20000mAh/3.2V(6S1P) 13500mAh/3.2V(6S1P) Actual total capacity 19.2V20Ah(384W)/19.2V13.5Ah(259W)
Input	1. DC5521 12V-24V/1-5A The power adapter 2. DC5521 12V-24V/1-5A Vehicle charging 3. DC5521 12V-24V/1-5A Solar panels
Output	1. AC220V or 110V,300/600W,50Hz/60Hz 2. DCVehicle charging +DC Connect 12V-10A/120W Total power 3. USB-Ax2 QC3.0 Fast charging 5V-3A,9V-2A,12V-1.5A/18W Total power 4. USB-C1 PD/QC3.0 Fast charging 5V-3A,9V-2A, 12V-1.5A/18W Total power 5. USB-C2 PD Fast charging 5V-3A,9V-3A,12V-3A,15V-3A,20V-3A/100W Total power 6. LED Light 1W Highlight,Level 2 dimming and SOS Shiny
Electric core	Lithium iron 34185/34155 cylindrical type
Size	270*210*210mm
Material	PC+V0 flame retardant
Color	Customizable color
Product weight	About 6.5kg
Package size	345*285*280mm
Authentication test report	GB4943.1、CE、FCC、ROHS、UN38.3、MSDS、UL、CB、BIS、PSE

Item No: PS-300/600W-2



Item No: PS-300/600W-3



Product Specification	
Capacity	20000mAh/3.2V(6S1P) 13500mAh/3.2V(6S1P) Actual total capacity 19.2V20Ah(384W)/19.2V13.5Ah(259W)
Input	1. DC5521 12V-24V/1-5A The power adapter 2. DC5521 12V-24V/1-5A Vehicle charging 3. DC5521 12V-24V/1-5A Solar panels
Output	1. AC220V or 110V,300/600W,50Hz/60Hz 2. DCVehicle charging +DC Connect 12V-10A/120W Total power 3. USB-Ax2 QC3.0 Fast charging 5V-3A,9V-2A,12V-1.5A/18W Total power 4. USB-C1 PD/QC3.0 Fast charging 5V-3A,9V-2A, 12V-1.5A/18W Total power 5. USB-C2 PD Fast charging 5V-3A,9V-3A,12V-3A,15V-3A,20V-3A/100W Total power 6. LED Light 1W Highlight,Level 2 dimming and SOS Shiny
Electric core	Lithium iron 34185/34155 cylindrical type
Size	270*210*220mm
Material	PC+V0 flame retardant
Color	Customizable color
Product weight	About 6.5kg
Package size	345*285*280mm
Authentication test report	GB4943.1, CE, FCC, ROHS, UN38.3, MSDS, UL, CB, BIS, PSE

Product Specification	
Capacity	20000mAh/3.2V(6S1P) 13500mAh/3.2V(6S1P) Actual total capacity 19.2V20Ah(384W)/19.2V13.5Ah(259W)
Input	1. DC5521 12V-24V/1-5A The power adapter 2. DC5521 12V-24V/1-5A Vehicle charging 3. DC5521 12V-24V/1-5A Solar panels
Output	1. AC220V or 110V,300/600W,50Hz/60Hz 2. DCVehicle charging +DC Connect 12V-10A/120W Total power 3. USB-Ax2 QC3.0 Fast charging 5V-3A,9V-2A,12V-1.5A/18W Total power 4. USB-C1 PD/QC3.0 Fast charging 5V-3A,9V-2A, 12V-1.5A/18W Total power 5. USB-C2 PD Fast charging 5V-3A,9V-3A,12V-3A,15V-3A,20V-3A/100W Total power 6. LED Light 1W Highlight,Level 2 dimming and SOS Shiny
Electric core	Lithium iron 34185/34155 cylindrical type
Size	270*210*210mm
Material	PC+V0 flame retardant
Color	Customizable color
Product weight	About 6.5kg
Package size	345*285*280mm
Authentication test report	GB4943.1, CE, FCC, ROHS, UN38.3, MSDS, UL, CB, BIS, PSE

Item No: PS-300/600W-4



Product Specification	
Capacity	20000mAh/3.2V(6S1P) 13500mAh/3.2V(6S1P) Actual total capacity 19.2V20Ah(384W)/19.2V13.5Ah(259W)
Input	1. DC5521 12V-24V/1-5A The power adapter 2. DC5521 12V-24V/1-5A Vehicle charging 3. DC5521 12V-24V/1-5A Solar panels
Output	1. AC220V or 110V,300/600W,50Hz/60Hz 2. DCVehicle charging +DC Connect 12V-10A/120W Total power 3. USB-Ax2 QC3.0 Fast charging 5V-3A,9V-2A,12V-1.5A/18W Total power 4. USB-C1 PD/QC3.0 Fast charging 5V-3A,9V-2A, 12V-1.5AZ18W Total power 5. USB-C2 PD Fast charging 5V-3A,9V-3A,12V-3A,15V-3A,20V-3A/100W Total power 6. LED Light 1W Highlight,Level 2 dimming and SOS Shiny
Electric core	Lithium iron 34185/34155 cylindrical type
Size	270*210*188mm
Material	PC+V0 flame retardant
Color	Customizable color
Product weight	About 6.5kg
Package size	345*285*280mm
Authentication test report	GB4943.1, CE, FCC, ROHS, UN38.3, MSDS, UL, CB, BIS, PSE

Item No: PS-300/600W-5



Product Specification	
Capacity	20000mAh/3.2V(6S1P) 13500mAh/3.2V(6S1P) Actual total capacity 19.2V20Ah(384W)/19.2V13.5Ah(259W)
Input	1. DC5521 12V-24V/1-5A The power adapter 2. DC5521 12V-24V/1-5A Vehicle charging 3. DC5521 12V-24V/1-5A Solar panels
Output	1. AC220V or 110V,300/600W,50Hz/60Hz 2. DCVehicle charging +DC Connect 12V-10A/120W Total power 3. USB-Ax2 QC3.0 Fast charging 5V-3A,9V-2A,12V-1.5A/18W Total power 4. USB-C1 PD/QC3.0 Fast charging 5V-3A,9V-2A, 12V-1.5AZ18W Total power 5. USB-C2 PD Fast charging 5V-3A,9V-3A,12V-3A,15V-3A,20V-3A/100W Total power 6. LED Light 1W Highlight,Level 2 dimming and SOS Shiny
Electric core	Lithium iron 34185/34155 cylindrical type
Size	270*210*234mm
Material	PC+V0 flame retardant
Color	Customizable color
Product weight	About 6.5kg
Package size	345*285*280mm
Authentication test report	GB4943.1, CE, FCC, ROHS, UN38.3, MSDS, UL, CB, BIS, PSE

Item No: PS-600/1200W



Item No: PS-2000W



Product Specification	
Capacity	26000mAh/3.2V(6S2P) 13500mAh/3.2V(6S2P) Actual total capacity 19.2V52Ah(998W)/19.2V27Ah(518W)
Input	1. DC5521 12V-24V/1-5A The power adapter 2. DC5521 12V-24V/1-5A Vehicle charging 3. DC5521 12V-24V/1-5A Solar panels
Output	1. AC220V or 110V,600/1200W,50Hz/60Hz 2. DCVehicle charging +DC Conned 12V-10A/120W Total power 3. USB-Ax2 QC3.0 Fast charging 5V-3A,9V-2A,12V-1.5A/18W Total power 4. USB-C1 PD7QC3.0 Fast charging 5V-3A,9V-2A,12V-1.5A/18W Total power 5. USB-C2 PD Fast charging 5V-3A,9V-3A, 12V-3A, 15V-3A.20V-3A/100W Total power 6. LED Light 1W Highlight,Level 2 dimming and SOS Shiny
Electric core	Lithium iron 40159/34155 cylindrical type
Size	280*245*250mm
Material	PC+VO flame retardant
Color	Customizable color
Product weight	About 11.2kg
Package size	350*320*345mm
Authentication test report	GB4943.1, CE, FCC, ROHS, UN38.3, MSDS, UL, CB, BIS, PSE

Product Specification	
Capacity	26000mAh/3.2V(16S2P) 13500mAh/3.2V(16S2P) Actual total capacity 51.2V52Ah(2662W)/51.2V27Ah(1382W)
Input	1. DC5521 12V-24V/1-5A The power adapter 2. DC5521 12V-24V/1-5A Vehicle charging 3. DC5521 12V-24V/1-5A Solar panels
Output	1. AC220V or 110V,2000W,50Hz/60Hz 2. DCVehicle charging +DC Conned 12V-10A/120W Total power 3. USB-Ax2 QC3.0 Fast charging 5V-3A,9V-2A,12V-1.5A/18W Total power 4. USB-C1 PD7QC3.0 Fast charging 5V-3A,9V-2A,12V-1.5A/18W Total power 5. USB-C2 PD Fast charging 5V-3A,9V-3A, 12V-3A, 15V-3A.20V-3A/100W Total power 6. LED Light 1W Highlight,Level 2 dimming and SOS Shiny
Electric core	Lithium iron 40159/34155 cylindrical type
Size	462*252*333mm
Material	PC+VO flame retardant
Color	Customizable color
Product weight	About 24 kg
Package size	440*345*350mm
Authentication test report	GB4943.1, CE, FCC, ROHS, UN38.3, MSDS, UL, CB, BIS, PSE